

H Range

Cell dimensions

Cell Type	Capacity at the 5 hr rate (Ah)	Cell Dimensions in mm					Cell connection bolt size	Container size reference	Reserve electrolyte cc/cell	Approx Weight(Kg) 1.2 V Block
		Height	Width	Length						
				1.2 V L (1)	2.4 V L (2)	3.6 V L (3)				
KBH 9 P	9	264	123	69	100	M8	B21-1	90	1.1	
KBH 13 P	13	264	123	79	115	M8	B22-1	110	1.5	
KBH 17 P	17	264	123	79	115	M8	B22-1	110	1.9	
KBH 20 P	20	264	123	103	151	M8	B23-1	145	2.6	
KBH 28 P	28	264	123	127	187	M8	B24-1	185	3.3	
KBH 34 P	34	264	123	127	187	M8	B24-1	185	3.8	
KBH 40 P	40	405	195	79	115	M10	B45-1	280	4.8	
KBH 50 P	50	405	195	79	115	M10	B45-1	280	5.4	
KBH 54 P	54	349	195	103	151	M10	B33-1	380	5.5	
KBH 59 P	59	349	195	103	151	M10	B33-1	380	5.6	
KBH 64 P	64	349	195	127	187	M10	B32-1	515	6.0	
KBH 69 P	69	349	195	127	187	M10	B32-1	515	6.2	
KBH 79 P	79	349	195	127	187	M10	B32-1	515	6.8	
KBH 88 P	88	349	195	159	232	M10	B31B-1	650	7.8	
KBH 98 P	98	349	195	159	232	M10	B31B-1	650	8.4	
KBH 103 P	103	349	195	159	232	M10	B31B-1	650	9.4	
KBH 110 P	110	349	195	183	268	M10	B31-1	745	9.5	
KBH 118 P	118	349	195	183	268	M10	B31-1	745	9.6	
KBH 127 P	127	349	195	132	252	372	2 x M10	1030	11.0	
KBH 137 P	137	349	195	132	252	372	2 x M10	1030	12.0	
KBH 140 P	140	349	195	132	252	372	2 x M10	1030	12.3	
KBH 157 P	157	349	195	132	252	372	2 x M10	1030	13.4	
KBH 170 P	170	349	195	132	252	372	2 x M10	1030	14.5	
KBH 177 P	177	349	195	159			2 x M10	B31B-2	1300	15.6
KBH 185 P	185	349	195	159			2 x M10	B31B-2	1300	16.1
KBH 196 P	196	349	195	159			2 x M10	B31B-2	1300	16.8
KBH 206 P	206	349	195	159			2 x M10	B31B-2	1300	17.4
KBH 218 P	218	349	195	183			2 x M10	B31-2	1490	18.6
KBH 236 P	236	349	195	183			2 x M10	B31-2	1490	19.6
KBH 245 P	245	349	195	183			2 x M10	B31-2	1490	20.0
KBH 265 P	265	349	195	232			3 x M10	B31B-3	1950	23.4
KBH 275 P	275	349	195	232			3 x M10	B31B-3	1950	24.0
KBH 294 P	294	349	195	232			3 x M10	B31B-3	1950	25.2
KBH 310 P	310	349	195	232			3 x M10	B31B-3	1950	26.0
KBH 330 P	330	349	195	268			3 x M10	B31-3	2235	26.7
KBH 353 P	353	349	195	268			3 x M10	B31-3	2235	28.0
KBH 362 P	362	349	195	268			3 x M10	B31-3	2235	28.9
KBH 393 P	393	349	195	304			4 x M10	B31B-4	2600	33.6
KBH 410 P	410	349	195	304			4 x M10	B31B-4	2600	34.0
KBH 420 P	420	349	195	352			4 x M10	B31-4	2980	36.0
KBH 445 P	445	349	195	352			4 x M10	B31-4	2980	36.8
KBH 471 P	471	349	195	352			4 x M10	B31-4	2980	38.0
KBH 481 P	481	349	195	352			4 x M10	B31-4	2980	38.5
KBH 491 P	491	349	195	377			5 x M10	B31B-5	3250	41.8
KBH 515 P	515	349	195	377			5 x M10	B31B-5	3250	43.0
KBH 530 P	530	349	195	437			5 x M10	B31-5	3725	47.0
KBH 545 P	545	349	195	437			5 x M10	B31-5	3725	47.5
KBH 570 P	570	349	195	437			5 x M10	B31-5	3725	48.0
KBH 590 P	590	349	195	437			5 x M10	B31-5	3725	48.5
KBH 615 P	615	405	195	377			5 x M10	B41B-5	3250	49.8
KBH 640 P	640	405	195	377			5 x M10	B41B-5	3250	51.0
KBH 670 P	670	405	195	377			5 x M10	B41B-5	3250	52.5
KBH 695 P	695	405	195	437			5 x M10	B41-5	3725	54.8
KBH 705 P	705	405	195	437			5 x M10	B41-5	3725	55.2
KBH 725 P	725	405	195	437			5 x M10	B41-5	3725	56.3
KBH 765 P	765	405	195	437			5 x M10	B41-5	3725	58.5
KBH 805 P	805	405	195	522			6 x M10	B41-6	4470	64.0
KBH 840 P	840	405	195	522			6 x M10	B41-6	4470	65.5
KBH 860 P	860	405	195	522			6 x M10	B41-6	4470	66.5
KBH 890 P	890	405	195	522			6 x M10	B41-6	4470	67.7
KBH 920 P	920	405	195	522			6 x M10	B41-6	4470	69.3
KBH 930 P	930	405	195	522			6 x M10	B41-6	4470	69.5

❖ Block types starting from KBH 88 P shall have handles.

❖ Cell ranges other than listed above can be supplied on request. The Parameters and performance will proportionately change.