

L Range

Cell dimensions

Cell Type	Capacity at the 5 hr rate (Ah)	Cell Dimensions in mm					Cell connection bolt size	Container size reference	Reserve electrolyte cc/cell	Approx Weight(Kg) 1.2 V Block
		Height	Width	Length						
				1.2 V L (1)	2.4 V L (2)	3.6 V L (3)				
KBL 8 P	8	264	123		79	115	M8	B22-1	110	0.9
KBL 17 P	17	264	123		79	115	M8	B22-1	110	1.2
KBL 21 P	21	264	123		79	115	M8	B22-1	110	1.4
KBL 32 P	32	264	123		103	151	M8	B23-1	145	2.0
KBL 38 P	38	264	123		103	151	M8	B23-1	145	2.4
KBL 46 P	46	264	123		127	187	M8	B24-1	185	3.4
KBL 50 P	50	405	195		79	115	M10	B45-1	280	4.0
KBL 64 P	64	405	195		79	115	M10	B45-1	280	4.5
KBL 73 P	73	405	195		79	115	M10	B45-1	280	4.8
KBL 80 P	80	405	195		79	115	M10	B45-1	280	5.1
KBL 90 P	90	405	195		79	115	M10	B45-1	280	5.4
KBL 102 P	102	349	195		103	151	M10	B33-1	380	5.7
KBL 118 P	118	405	195		115	169	M10	B42A-1	450	7.3
KBL 128 P	128	349	195		127	187	M10	B32-1	515	7.3
KBL 140 P	140	405	195		115	169	M10	B42A-1	450	7.8
KBL 155 P	155	405	195		127	187	M10	B42-1	515	8.2
KBL 173 P	173	405	195		127	187	M10	B42-1	515	8.5
KBL 200 P	200	405	195		159	232	M10	B41B-1	650	10.5
KBL 214 P	214	405	195		159	232	M10	B41B-1	650	10.7
KBL 220 P	220	405	195		183	268	M10	B41-1	745	11.2
KBL 256 P	256	405	195		183	268	M10	B41-1	745	12.7
KBL 280 P	280	405	195	120	228	336	2 x M10	B42A-2	900	15.6
KBL 304 P	304	405	195	120	228	336	2 x M10	B42A-2	900	15.9
KBL 320 P	320	405	195	132	252	372	2 x M10	B42-2	1030	16.5
KBL 346 P	346	405	195	132	252	372	2 x M10	B42-2	1030	16.7
KBL 360 P	360	405	195	159	304		2 x M10	B41B-2	1300	19.8
KBL 390 P	390	405	195	159	304		2 x M10	B41B-2	1300	20.2
KBL 400 P	400	405	195	159	304		2 x M10	B41B-2	1300	20.8
KBL 429 P	429	405	195	159	304		2 x M10	B41B-2	1300	21.2
KBL 450 P	450	405	195	183	352		2 x M10	B41-2	1490	23.5
KBL 465 P	465	405	195	183	352		2 x M10	B41-2	1490	24.2
KBL 490 P	490	405	195	183			2 x M10	B41-2	1490	24.9
KBL 510 P	510	405	195	183			2 x M10	B41-2	1490	25.2
KBL 535 P	535	405	195	232			3 x M10	B41B-3	1950	27.4
KBL 570 P	570	405	195	232			3 x M10	B41B-3	1950	28.8
KBL 585 P	585	405	195	232			3 x M10	B41B-3	1950	30.2
KBL 620 P	620	405	195	232			3 x M10	B41B-3	1950	31.0
KBL 645 P	645	405	195	232			3 x M10	B41B-3	1950	31.6
KBL 675 P	675	405	195	268			3 x M10	B41-3	2235	35.6
KBL 700 P	700	405	195	268			3 x M10	B41-3	2235	36.1
KBL 770 P	770	405	195	268			3 x M10	B41-3	2235	38.2
KBL 800 P	800	405	195	304			4 x M10	B41B-4	2600	41.8
KBL 830 P	830	405	195	304			4 x M10	B41B-4	2600	42.5
KBL 860 P	860	405	195	304			4 x M10	B41B-4	2600	42.8
KBL 920 P	920	405	195	352			4 x M10	B41-4	2980	48.0
KBL 970 P	970	405	195	352			4 x M10	B41-4	2980	49.2
KBL 1020 P	1020	405	195	352			4 x M10	B41-4	2980	50.8
KBL 1040 P	1040	405	195	377			5 x M10	B41B-5	3250	52.4
KBL 1070 P	1070	405	195	377			5 x M10	B41B-5	3250	53.5
KBL 1140 P	1140	405	195	437			5 x M10	B41-5	3725	59.0
KBL 1220 P	1220	405	195	437			5 x M10	B41-5	3725	61.3
KBL 1240 P	1240	405	195	437			5 x M10	B41-5	3725	61.8
KBL 1280 P	1280	405	195	437			5 x M10	B41-5	3725	63.5
KBL 1320 P	1320	405	195	522			6 x M10	B41-6	4470	70.0
KBL 1360 P	1360	405	195	522			6 x M10	B41-6	4470	71.1
KBL 1400 P	1400	405	195	522			6 x M10	B41-6	4470	72.0
KBL 1480 P	1480	405	195	522			6 x M10	B41-6	4470	74.0
KBL 1540 P	1540	405	195	522			6 x M10	B41-6	4470	75.0

❖ Block types starting from KBL 200 P shall have handles.

❖ Cell ranges other than listed above can be supplied on request. The Parameters and performance will proportionately change.