

# M Range

## Cell dimensions

Cell Type	Capacity at the 5 hr rate (Ah)	Cell Dimensions in mm					Cell connection bolt size	Container size reference	Reserve electrolyte cc/cell	Approx Weight(Kg) 1.2 V Block
		Height	Width	Length						
				1.2 V L (1)	2.4 V L (2)	3.6 V L (3)				
KBM 12 P	12	264	123	69	100	M8	B21-1	90	1.1	
KBM 16 P	16	264	123	69	100	M8	B21-1	90	1.3	
KBM 23 P	23	264	123	79	115	M8	B22-1	110	1.6	
KBM 26 P	26	264	123	79	115	M8	B22-1	110	1.8	
KBM 34 P	34	264	123	103	151	M8	B23-1	145	2.4	
KBM 44 P	44	264	123	127	187	M8	B24-1	185	3.5	
KBM 48 P	48	264	123	127	187	M8	B24-1	185	3.7	
KBM 57 P	57	405	195	79	115	M10	B45-1	280	4.2	
KBM 67 P	67	405	195	79	115	M10	B45-1	280	4.5	
KBM 75 P	75	405	195	79	115	M10	B45-1	280	5.0	
KBM 84 P	84	405	195	79	115	M10	B45-1	280	5.1	
KBM 95 P	95	405	195	94	137	M10	B44-1	350	5.6	
KBM 112 P	112	405	195	94	137	M10	B44-1	350	6.1	
KBM 138 P	138	405	195	115	169	M10	B42A-1	450	7.5	
KBM 148 P	148	405	195	127	187	M10	B42-1	515	8.0	
KBM 161 P	161	405	195	127	187	M10	B42-1	515	8.6	
KBM 184 P	184	405	195	159	232	M10	B41B-1	650	9.8	
KBM 195 P	195	405	195	183	268	M10	B41-1	745	11.1	
KBM 208 P	208	405	195	183	268	M10	B41-1	745	11.4	
KBM 231 P	231	405	195	183	268	M10	B41-1	745	11.9	
KBM 277 P	277	405	195	120	228	2 x M10	B42A-2	900	14.4	
KBM 310 P	310	405	195	132	252	2 x M10	B42-2	1030	16.6	
KBM 323 P	323	405	195	132	252	2 x M10	B42-2	1030	17.2	
KBM 350 P	350	405	195	159	304	2 x M10	B41B-2	1300	18.8	
KBM 369 P	369	405	195	159	304	2 x M10	B41B-2	1300	19.6	
KBM 375 P	375	405	195	183	352	2 x M10	B41-2	1490	20.2	
KBM 400 P	400	405	195	183	352	2 x M10	B41-2	1490	22.4	
KBM 415 P	415	405	195	183		2 x M10	B41-2	1490	22.8	
KBM 438 P	438	405	195	183		2 x M10	B41-2	1490	23.2	
KBM 461 P	461	405	195	183		2 x M10	B41-2	1490	24.0	
KBM 480 P	480	405	195	232		3 x M10	B41B-3	1950	27.5	
KBM 495 P	495	405	195	232		3 x M10	B41B-3	1950	28.0	
KBM 540 P	540	405	195	232		3 x M10	B41B-3	1950	29.0	
KBM 555 P	555	405	195	232		3 x M10	B41B-3	1950	29.4	
KBM 590 P	590	405	195	268		3 x M10	B41-3	2235	33.0	
KBM 625 P	625	405	195	268		3 x M10	B41-3	2235	34.2	
KBM 650 P	650	405	195	268		3 x M10	B41-3	2235	35.0	
KBM 690 P	690	405	195	268		3 x M10	B41-3	2235	35.4	
KBM 705 P	705	405	195	268		3 x M10	B41-3	2235	35.9	
KBM 740 P	740	405	195	304		4 x M10	B41B-4	2600	39.2	
KBM 770 P	770	405	195	352		4 x M10	B41-4	2980	43.5	
KBM 805 P	805	405	195	352		4 x M10	B41-4	2980	44.2	
KBM 830 P	830	405	195	352		4 x M10	B41-4	2980	44.5	
KBM 870 P	870	405	195	352		4 x M10	B41-4	2980	46.0	
KBM 890 P	890	405	195	352		4 x M10	B41-4	2980	46.8	
KBM 920 P	920	405	195	352		4 x M10	B41-4	2980	47.6	
KBM 940 P	940	405	195	352		4 x M10	B41-4	2980	48.2	
KBM 965 P	965	405	195	372		6 x M10	B42-6	3090	51.0	
KBM 1000 P	1000	405	195	378		5 x M10	B41B-5	3250	51.2	
KBM 1040 P	1040	405	195	437		5 x M10	B41-5	3725	55.7	
KBM 1100 P	1100	405	195	437		5 x M10	B41-5	3725	59.0	
KBM 1150 P	1150	405	195	437		5 x M10	B41-5	3725	62.7	
KBM 1180 P	1180	405	195	437		5 x M10	B41-5	3725	63.2	
KBM 1225 P	1225	405	195	522		6 x M10	B41-6	4470	66.2	
KBM 1270 P	1270	405	195	522		6 x M10	B41-6	4470	67.8	
KBM 1330 P	1330	405	195	522		6 x M10	B41-6	4470	69.2	
KBM 1390 P	1390	405	195	522		6 x M10	B41-6	4470	70.8	
KBM 1460 P	1460	405	195	522		6 x M10	B41-6	4470	72.2	

❖ Block types starting from KBM 184 P shall have handles.

❖ Cell ranges other than listed above can be supplied on request. The Parameters and performance will proportionately change.